

IN THE CLAIMS:

1. (currently amended) A collapsible container comprising a base, a top ring and a wall peripherally fixed to said base and top ring and extending therebetween, said container being adjustable between an expanded position with the top ring spaced upward from said base and forming a container interior, and a collapsed position with said top ring surrounding said base in outwardly spaced substantially concentric relation thereto, said wall comprising multiple upwardly extending peripherally continuous sections which, in the expanded position of said container, angle alternately outward and inward relative to the container interior, said sections, in the collapsed position of said container, being folded on each other and concentrically received generally between the base and the top ring with the sections encircling the base and in turn being encircled by said top ring, wherein the container includes flexure zones joining adjacent sections, the adjacent sections being of limited flexibility relative to the flexure zones, and wherein each flexure zone is independently activatable for movement between a first, open natural state in which adjacent sections are unfolded, and a second, closed natural state in which the respective adjacent sections are folded; and wherein the container is adjustable to a fixed, partially expanded position between said expanded position and

said collapsed position.

2-58. (cancelled).

59. (currently amended) A collapsible container comprising:
a base, a top ring, and a wall extending between the top
ring and the base, wherein the wall has at least a first
section, ~~and~~ a second section, and a third section, wherein
the first section is adjacent the second section and wherein
the second section is adjacent the third section, ~~and~~ a first
flexure zone disposed between the first section and second
section, a second flexure zone disposed between the second
section and the third section, and a third flexure zone
disposed between the first section and the base, wherein the
container is adjustable between at least an expanded position
forming an interior and having a first
volume, a partially expanded position having a second volume
less than the first volume, and a collapsed position with said
top ring surrounding said base in outwardly spaced
substantially concentric relation thereto with the sections
being folded and concentrically received generally between the
base and the top ring with the sections encircling the base
and in turn being encircled by said top ring; wherein in the
expanded position, the first section angles outward relative

to the interior, and the second section angles inward relative to the interior; and wherein said container is stable in each of said positions and wherein positive force is required to adjust the container from the partially expanded position to the expanded position, and to adjust the container from the partially expanded position to the collapsed position.

60. (previously presented) The container of claim 59 wherein in the expanded condition, the first and second sections form an obtuse angle.

61. (cancelled).

62. (previously presented) The container of claim 59 wherein in the collapsed condition, the first and second sections form an acute angle.

63-68 (cancelled).

69. (new) The container of claim 59, wherein the first and second sections each have a thickness greater than the thickness of the first flexure zone.

70. (new) The container of claim 59, wherein the first flexure zone is substantially arcuate.

71. (new) The container of claim 59, further comprising a fourth flexure zone disposed between the third section and the top ring.

72. (new) The container of claim 59, wherein in the expanded position, the third section angles outward relative to the interior.

73. (new) The container of claim 59, wherein the top ring includes an annular flange extending outwardly therefrom.

74. (new) The container of claim 59, wherein in the collapsed position, the first, second, and third sections are folded and concentrically disposed between the base and the top ring.

75. (new) The container of claim 59, wherein in the collapsed position, the first section and the second section form a first angled opening, wherein the base at least partially defines a support plane, and wherein the centerline of the first angled opening is substantially perpendicular to the

support plane.

76. (new) The container of claim 59, wherein in the collapsed condition, the folded portion of the wall and the base are each at an elevation, wherein the lowest elevation of the base is lower than the lowest elevation of the folded portion of the wall.

77. (new) The container of claim 59, wherein a portion of the wall overlays a portion of the base.

78. (new) The container of claim 59, wherein the wall is molded in the collapsed position.

79. (new) The container of claim 59, wherein the base is non-permeable.

80. (new) The container of claim 59, wherein the first, second, and third flexure zones each have a thickness, and wherein the thickness of the first, second, and third flexure zones is substantially equal.

81. (new) The container of claim 1, wherein in the expanded position, said sections form an obtuse angle.

82. (new) The container of claim 1, wherein in the collapsed position, said sections form an acute angle.

83. (new) The container of claim 1, wherein said sections each have a thickness greater than the thickness of the flexure zones.

84. (new) The container of claim 1, wherein one of said flexure zones is disposed between the top ring and one of said sections.

85. (new) The container of claim 1, wherein one of said flexure zones is disposed between the base and one of said sections.

86. (new) The container of claim 1, wherein the top ring includes an annular flange extending outwardly therefrom.

87. (new) The container of claim 1, wherein in the collapsed position, the folded sections are concentrically disposed

between the base and the top ring.

88. (new) The container of claim 1, wherein in the collapsed position, the folded sections are at an elevation wherein the lowest elevation of the base is lower than the lowest elevation of the folded section.

89. (new) The container of claim 1, wherein a portion of the wall overlays a portion of the base.

90. (new) The container of claim 1, wherein the wall is molded in the collapsed position.

91. (new) the container of claim 1, wherein the base is non-permeable.